


ALUMINIUM LED PROFIELEN (ALUMINIUM LED PROFILES)

Slim line, opbouw (surface mount)



Slim line, opbouw (surface mount) 7mm



Opbouw aluminium LED profiel. Gemaakt van geanodiseerd aluminium. Het LED aluminium profiel zorgt naast de mechanische bescherming ook voor de koeling van de LED's. Verkrijgbaar in lengtes van 1 en 2 meter met transparante, semi-transparante of melkwitte lens. Gemaakt uit UV-bestendig geëxtrudeerd polycarbonaat. Eindkappen en montagebeugels separaat te bestellen.

Toepassingsgebieden: keukenkasten, interieurbouw, accentverlichting, winkelplanken, tentoonstellingen.

Surface mounted LED aluminum profile. Made of anodized aluminum. Next to the mechanical protection, the aluminum LED profile also provides sufficient cooling for the LED's. Available in lengths of 1 and 2 meter with transparent, semi-transparent or milky white lens which is made of UV-resistant extruded polycarbonate. End caps and mounting brackets can be ordered separately.

Applications: kitchen cabinets, interior design, accent lighting, store shelves, exhibitions, etc.

4629000 / ..

Lenskleur
Lens color

- 0: Transparante lens, 1mtr
Transparent lens, 1 mtr
- 1: Melkwitte lens, 1mtr
Milky white lens, 1mtr
- 2: Semi-transparante lens, 1mtr
Semi-transparent, 1mtr
- 3: Transparante lens, 2mtr
Transparent lens, 2 mtr
- 4: Melkwitte lens, 2mtr
Milky white lens, 2mtr
- 5: Semi-transparante lens, 2 mtr
Semi-transparent, 2mtr



46290006

Eindkap met draaddoorvoer
End cap with cable hole



46290007

Eindkap
End cap




46290008

Montagebeugel
Mounting bracket



Slim line, opbouw (surface mount) 15mm



Opbouw aluminium LED profiel. Gemaakt van geanodiseerd aluminium. Het LED aluminium profiel zorgt naast de mechanische bescherming ook voor de koeling van de LED's. Verkrijgbaar in lengtes van 1 en 2 meter met transparante, semi-transparante of melkwitte lens. Gemaakt uit UV-bestendig geëxtrudeerd polycarbonaat. Eindkappen en montagebeugels separaat te bestellen.

Toepassingsgebieden: keukenkasten, interieurbouw, accentverlichting, winkelplanken, tentoonstellingen.

Surface mounted LED aluminum profile. Made of anodized aluminum. Next to the mechanical protection, the aluminum LED profile also provides sufficient cooling for the LED's. Available in lengths of 1 and 2 meter with transparent, semi-transparent or milky white lens which is made of UV-resistant extruded polycarbonate. End caps and mounting brackets can be ordered separately.

Applications: kitchen cabinets, interior design, accent lighting, store shelves, exhibitions, etc.

4629003 / ..

Lenskleur
Lens color

- 0: Transparante lens, 1mtr
Transparent lens, 1 mtr
- 1: Melkwitte lens, 1mtr
Milky white lens, 1mtr
- 2: Semi-transparante lens, 1mtr
Semi-transparent, 1mtr
- 3: Transparante lens, 2mtr
Transparent lens, 2 mtr
- 4: Melkwitte lens, 2mtr
Milky white lens, 2mtr
- 5: Semi-transparante lens, 2 mtr
Semi-transparent, 2mtr



46290036

Eindkap met draaddoorvoer
End cap with cable hole



46290037

Eindkap
End cap



46290038

Montagebeugel
Mounting bracket



Slim line, opbouw (surface mount) 7mm

PROLUMIA®



Slim line, opbouw (surface mount) 15mm

PROLUMIA®

